

☒ **CTL Provisional DECISION SHEET (PDSH)**
☐ **CTL DECISION SHEET (DSH)**

Standard(s) (incl. year)	Subclause(s)	Tracking No.
IEC 60335-2-75:2024	5.7	2288
Category	7.12.1	
HOUS	7.12.101	
Subject	Keywords	Developed by
Indications of ambient temperature for operation	Recommended ambient temperature.	ETF 1
Question		
Q1: What is the recommended ambient temperature mentioned in clause 5.7?		
Q2: What is the recommended maximum ambient temperature in clause 5.7?		
Decision		
A1: the recommended ambient temperature is a temperature not less than the indicated minimum ambient temperature and not more than the indicated maximum ambient temperature as required by clauses 7.12.1 and 7.12.101.		
A2: the recommended maximum ambient temperature is the indicated maximum ambient temperature with the deviation of +5/-0 °C.		
E.g., if the instructions specifies that the appliance shall be operated at an ambient temperature range of 20-35 °C, clause 5.7 states that the specific tests shall be performed at 35 °C +5/-0°C.		
Explanatory notes		
<u>Enquiry:</u>		
Date:	2025-06	
<u>PDSH:</u>		
Year of publication:	2025	
To be approved at CTL plenary:	2026	
<u>DSH</u>		
Publication date:	---	
<p>Clause 7.12.1 and 7.12.101</p> <p>The installation and maintenance instruction shall state the maximum and minimum ambient temperatures for correct operation.</p> <p>Clause 5.7</p> <p>For appliances with a recommended ambient temperature above 25°C, the tests of clause 10, clause 11 (except clause 11.101) and Clause 13 are carried out at the recommended maximum ambient temperature with deviation of +5/-0 °C.</p>		